

EXIDE

Sprinter P/XP
Design Life 10-12 Jahre

- Hervorragende Hochstromeigenschaften
Für Gefahrenmeldetechnik, USV, Sicherheitsbeleuchtung



Artikel Nr.	Type	Nenn- spannung V	Leistung	Nennkapazität	Maße mm max.			Höhe inkl. Verbinder max. mm	An- schluss	Gewicht kg
			10 Min. 1,60 V/C 25°C W / Block	C10 1,80 V/Z 25°C Ah	L	B	H			
20.05664	P6V1700	6	2210	122	273	167	191	191	M-M8	25,0
20.05666	XP6V2800	6	2780	195	309	172	223	241	F-M6	30,5
20.05661	P12V600	12	791	24,0	169	128	175	175	M-M6	9,50
20.05660	P12V875	12	1157	41,0	200	169	176	176	M-M6	14,5
20.05665	XP12V1800	12	1840	56,4	220	172	219	235	F-M6	21,0
20.05168	P12V1575	12	61,0	43,8	273	167	191	235	F-M6	24,0
20.05176	XP12V2500	12	2450	69,5	262	172	223	239	F-M6	26,0
20.05177	XP12V3000	12	3040	92,8	309	172	223	239	F-M6	31,0