

## 3 Volt Lithium MnO<sub>2</sub> – Round cells

Varta

Nominal Voltage: 3,0 V



High open circuit and load voltage (above 3,0 V per cell)  
 Superior shelf life and operational life (Up to 10 years and more)  
 Low self discharge (less than 1% per year at RT)  
 Operation over a wide temperature range (-30° ~ +75%)

All Lithium Cells are recognized by UL-file number MH 13654.

For use as stand-by battery review the safety and handling instructions of the manufacturer.

Order no.	Type	mAh	Max. continuous discharge current mAh	Dimension mm	Weight g
20.09600	CR ½ AA	950	10	H 25,1 / Ø 14,7	11,5
20.09601	CR ½ AA/T	950	10	H 26 / Ø 14,7	11,5
20.09602	CR ½ AA/P	950	10	H 26 / Ø 14,7	11,5
20.09603	CR ½ AA/SLF	950	10	H 26 / Ø 14,7	11,5
20.09610	CR ⅔ AA	1350	15	H 33 / Ø 14,7	15
20.09611	CR ⅔ AA/T	1350	15	H 34 / Ø 14,7	15
20.09612	CR ⅔ AA/P	1350	15	H 34 / Ø 14,7	15
20.09613	CR ⅔ AA/SLF	1350	15	H 34 / Ø 14,7	15
20.09620	CR AA	2000	20	H 50 / Ø 14,7	21,5
20.09621	CR AA/T	2000	20	H 51 / Ø 14,7	21,5
20.09622	CR AA/P	2000	20	H 51 / Ø 14,7	21,5
20.09623	CR AA/SLF	2000	20	H 51 / Ø 14,7	21,5

### Possible tabs

